

MEDOR® Exp

On-line analysis & monitoring of sulfur compounds in natural gas and gaseous fuels for hazardous area



**Class 1 Div 2 group B,
C&D T4**

**Class 1, Div 2
group B, C&D T4**

Model: MEDOR Exp

Main applications:

Impurities detection in Natural Gas / LPG / Propane / Butane
Propellant gas
Catalyzer protection

Targeted compounds:

In standard : THT / H₂S / DMS / Mercaptans: MM / EM / IPM / TBM / NPM
In option: 2 BM / IBM / NBM

Main markets:

Petrochemical
Gas transportation
Process

Standard:

ASTM D7493-08, ASTM D5504-20
ISO 19739:2004, DIN 51855/7



SCAN or CLICK ME



Chromatotec® is specialized in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt).
Please visit our website for more details.

Updated: October 2025

THT

TBM

DMS

H₂S

Bu-SH

Me-SH

Et-SH

MEDOR[®] Exp



On-line analysis & monitoring of sulfur compounds in natural gas and gaseous fuels for hazardous area

Description:

The MEDOR[®] Exp is an industrial gas chromatograph for the analysis and monitoring of sulfur compounds in natural gas and gaseous fuels: H₂S, Mercaptans, Sulfides.

Two versions exist: ppm range or ppb range

Principle:

- Automatic sampling using a loop
- Loop injection by automatic valve on the column
- Isothermal gas chromatograph
- Detection of all compounds eluting from the column performed by Chromatotec's wet cell sulfur specific detector
- Signal provided by electrochemical reaction between the wet cell electrolyte and the sulfur compounds

Key points:

- Fully compliant with ASTM D 7493-08 : Standard Test Method for On-line Measurement of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatograph and Electrochemical Detection
 - Internal automatic calibration system allowing automatic validation of the data
 - Continuous monitoring with automatic online sampling
 - Analytical performances:
 - Specific and very sensitive to sulfur compounds
 - Results validation by automatic standard injection at each analysis
 - Long term stability using wet cell detector installed in reservoir
 - Extremely low maintenance
 - Very long life time detector, up to 10 years including electrolyte
 - Low gas consumption, can be reduced in option
 - More than 10 years data storage
 - No calibration cylinders required thanks to internal calibration tube
 - Automatic control with process device
 - Intelligence system with tunable and interactive alarms levels
 - Internal temperature and pressure monitoring
- Powerfull VISTACHROM Chromatotec[®] software:
- Remote monitoring & injection control
 - Full traceability with on board archiving of results and chromatograms
 - QC Set up and control of threshold alarms
 - Data export by MODBUS / 4-20 mA / 0-10 V
 - Time stamp results
 - On site direct access to the analyzer with LCD screen and touch pad or front panel

Options:

- Class 1 Div 1, group B, C & D with inert purge
- External multiple stream selector (up to 16 streams controlled by the analyzer)
- Calculation modules (Average / Statistics / Odor index...)
- Electric selection valve to reduce air consumption
- 24 V DC power supply, can work on battery or solar panel
- Vortex cooler (air consumption: depending of internal t°)
- Inert purge with N₂ for low consumption of purge gas with X - purge (can work on N₂ cylinders)
- Internal electric heater and/or cooler for temperature regulation of the Exp Cabinet with thermal insulation
- Automatic tank filling
- Sealproof detector

Technical specifications:

- Speciation and/or total sulfur

Detection limits:

- **MEDOR[®] Exp ppm:**
 - H₂S: 0,1 ppm (0,14 mg/m³)
- **MEDOR[®] Exp ppb:**
 - H₂S: 5 ppb (7,0 µg/m³) or DMS: 2 ppb (5,1 µg/m³)

Range adjustable, depending on application:

- 0/10 or 0/100 or 0/1000 ppm or ppb
- Calculation: total sulfur, total mercaptans...

Relative Standard Deviation:

- RSD < 3% on concentration over 48H.
- RSD < 0.5% on retention time over 48H.

Cycle Time:

- | | |
|-------------------------------------|--|
| • H ₂ S | 120 s |
| • H ₂ S/TOS/TS | 120 s |
| • THT | 180s (if only THT) |
| • H ₂ S, MM, EM | 300s |
| • H ₂ S, mercaptans, THT | 720 s |
| • H ₂ S, mercaptans, THT | 900 s with CALIB for validation of each analysis |

Supervisor:

- Embedd industrial computer Windows[®] based with LCD display
- 32 GB of hardware storage on SSD memory

Linearity:

- > 0.995 for all compounds

Communication:

- MODBUS communication protocol
- 4-20mA
- Ethernet
- 3G module (optional)

Gas supply for GC operation:

- Carrier: zero air or N₂ (3 bar): 4 ml/min. Use N₂ if THT is present
- CALIB: air or N₂ 50 ml/min
- Sample inlet 1 bar: 80 ml/min
- Pneumatic valve: 90 ml/commutation (0 ml in option)

Gas supply for Exp cabinet:

- If air used for dilution: 30 l/min in continue
- If nitrogen used for dilution: 500 l to purge the cabinet and < 0,5 l/min in continue to maintain overpressure

Power supply:

- Main: 230V / 115V or 50/60 Hz
- 24 V DC in option

Electrical consumption:

- 150 VA without options

Dimensions and Weight:

- Height: 800 mm
- Width: 600 mm
- Depth: 300 mm
- Net weight: 40 kg

To order:

MEDOR[®] Exp

Model:

Upon request

Chromatotec[®] is continuously improving its products, therefore these specifications are subject to change without notice



To contact us: sales@chromatotec.com

NORTH AMERICA
Houston-USA

EUROPE
Bordeaux- FRANCE

ASIA
Beijing-CHINA